WO 2005/078515 PCT/IB2004/052859

PHNT.040034

6

CLAIMS:

1. A display device (1) comprising an electro-optical medium (5) between a pair of substrates (2,3) arranged in opposite relation with respect to each other by spacer means (7), one of the substrates being provided with coloring materials within areas separated from each other by said spacer means.

5

- 2. A display device as in claim 1, in which said spacer means are opaque.
- 3. A display device as claimed in Claim 1, said spacer means comprising a two-part structure.

10

20

25

- 4. A display device as claimed in Claim 3, the part of the two –part structure at the substrate provided with coloring materials comprising opaque material.
- 5. A display device as claimed in Claim 1, the coloring materials being conductive
  - 6. A display device as claimed in Claim 1, the display device further comprising a sealing edge (9) and a (semi-closed) barrier (11) between a filling opening (10) at one 'sealing edge of the display device and a part between the part of the substrate provided with coloring materials and the other sealing edges.
  - 7. A method for manufacturing a display device (1) comprising an electro-optical medium (5) between a pair of substrates (2,3), said method comprising the steps of providing spacer means on a first substrate separating different areas from each other supplying a coloring material to at least one area providing a second substrate on the spacer means.
  - 8. A method as claimed in Claim 6 in which step a) comprises the steps of al) providing an inorganic part as part of said spacer means

PCT/IB2004/052859

WO 2005/078515

PHNT.040034

7

- a2) providing a further organic part as part of said spacer means.
- 9. A method as claimed in Claim 6 in which step a) comprises the steps of
- al) providing an opaque part as part of said spacer means
- 5 a2) providing a further part as part of said spacer means.
- 10. A method as claimed in Claim 7 which further comprises the step of providing a sealing edge and a barrier between a filling opening at one sealing edge of the display device and a part between the part of the substrate provided with coloring materials and the
  10 other sealing edges, filing the device with liquid crystal material and sealing the filling opening.